

CONFIGURABLE SAFETY CONTROLLERS

MOSAIC MO4L

Output expansion unit.

Output expansion unit with 4 safety outputs (PNP 400 mA), 4 relative inputs for external feedback contacts (EDM) and 4 status output.

Screw terminal blocks.

Compatible: M1S

Certifications:



Technical data:

Family	MOSAIC
Code	1100012
Safety level (SIL / PL)	SIL 3 - SILCL 3 according to IEC 61508 - IEC 62061 / PL e - Cat. 4 according to ISO 13849-1
Connections	Removable terminal blocks, screw contacts
Power supply (VDC)	24 ± 20%
Safety relay outputs	-
Safety outputs	4 single OSSD (or 2 pairs) PNP - 400mA at 24 VDC with protection against short circuit, overload and reverse polarity
CCF (ISO 13849-1)	80%
system MTTFd (ISO 13849-1) years	30 ... 100
PFHd (IEC 61508)	1,32E-08
Degree of protection	IP 20 for housing - IP 2X for terminal block
Operating temperature (°C)	From -10 to 55
Storage temperature (°C)	From -20 to +85
Programmable signalling outputs	4 PNP - 100mA
Test outputs	4
Start/Restart inputs and EDM	4
LED signalling	Output status and fault diagnostics
USB input	-
Housing for MCM	-
Connection with MSC BUS	yes
MSC connector provided	yes
Dimensions HxWxD (mm)	108 x 22,5 x 114,5
Fastening	Rail fastening according to EN 50022-35 standard
Packaging dimensions W x H x L (mm)	160 x 135 x 60
Gross weight (Kg)	0,24

Related products:

[MOSAIC CPM](#)

See technical drawing in the next page.

Technical drawing:

