



ball valves, female threaded, with standard actuators



controls	nominal voltage	running time motor		optional	Typ 225 (IP52)		
				S2			
2/3 point	24VAC/DC	< 20...35s		x	225S-024T-05		
				< 60...120s		x	225-024T-05
	230VAC/DC	< 20...35s		x	225S-230T-05		
				< 60...120s		x	225-230T-05
0(2)...10VDC 0(4)...20mA	24VAC/DC	< 20...35s		x	225CS-024T-05		
				< 60...120s		x	225C-024T-05
ball valve Typ	port	DN	Rp	Kvs			
BOFB151K0B		15	1/2"	1	x		
BOFB151K6B				1,6	x		
BOFB152K5B				2,5	x		
BOFB154K1B				4,1	x		
BOFB1510KB				10,1	x		
BOFB204K1B				4,1	x		
BOFB206K4B		20	3/4"	6,4	x		
BOFB2010KB				10,1	x		
BOFB256K4B				6,4	x		
BOBF2510KB		25	1"	10,1	x		
BOFB2516KB				16,2	x		
BOFB3210KB		32	1-1/4"	10,1		x	
BOFB3216KB				16,2		x	
BOFB3225KB				25,3		x	
BOFB4016KB				16,2		x	
BOFB4025KB		40	1-1/2"	25,3		x	
BOFB4040KB				40,5		x	
BOFB5025KB		50	2"	25,3		x	
BOFB5041KB				40,5		x	
BOFB5064KB				63,8		x	
BOLB151K0B					15	1/2"	1
BOLB151K6B		1,6	x				
BOLB152K5B		2,5	x				
BOLB154K1B		4,1	x				
BOLB1510KB		10,1	x				
BOLB204K1B		4,1	x				
BOLB206K4B		20	3/4"		6,4	x	
BOLB2010KB					10,1	x	
BOLB256K4B	6,4				x		
BOLB2510KB	25	1"	10,1		x		
BOLB2516KB			16,2		x		
BOLB3210KB	32	1-1/4"	10,1			x	
BOLB3216KB			16,2			x	
BOLB3225KB			25,3			x	
BOLB4016KB			16,2			x	
BOLB4025KB	40	1-1/2"	25,3			x	
BOLB4040KB			40,5			x	
BOLB5025KB	50	2"	25,3			x	
BOLB5041KB			40,5			x	
BOLB5064KB			63,8			x	
close off pressure = 1380kPa		max.fluide temperature			xxx°C		xxx°C